

Technical Bulletin

Alpina LivingStyle COMPOSITION

Ready-tinted wall emulsion.

Material

Purpose:

Top-quality interior paint for new and decoration coatings on all interior surfaces. Also suitable for use in high-sensitivity living areas, since no odours are emitted during application or drying.

LivingStyle COMPOSITION usually covers with just one coat, dries extremely quickly, allowing the painted rooms to be used again without having to wait.

Properties:

Water-soluble, eco-friendly and odourless. Ready tinted.

Diffusible. High coverage.

Easy to apply. Gloss level: matt.

Wet abrasion class 3 to DIN EN 13 300, corresponds to wash-resistance to DIN 53 778.

Gloss level: satin-finished.

Wet abrasion class 1 to DIN EN 13 300, corresponds to chafe-resistance according to DIN 53 778.

Product declaration to VdL-RL01:

Content: Polyvinyl acetate dispersion, titanium dioxide, colour pigments, silicates, calcium carbonate, water, additives, preservatives (Methylisothiazolinone/Benzisothiazolinone).

Advice for those allergic to isothiazolinone as well as additional information:

Alpina Hotline Tel. No. +49(0)1805 123888 (€ 0.14/min. from a Deutsche Telekom landline, different tariff for calls from mobile phones).

Bonding agent:

Synthetic dispersion to DIN 55 945.

Gloss level:

matt or satin-finished.

Shades:

18 matt shades, 12 satin-finished shades.

Safety advice:

Keep out of the reach of children.

Do not inhale spray dust or spray mist.

Ensure adequate ventilation during application and drying. Avoid eating, drinking and smoke while using the paint. In case of contact with the eyes or skin, rinse with plenty of water.

Do not allow the product to enter sewerage networks, watercourses or ground soil.

Further details: see safety data sheet.

Produce code for paints and lacquer:

M-DF01

Storage:

cool but frost-free.

Seal open drums tightly before storing.

Disposal:

Pass only completely empty drums for recycling. Liquid material remnants can be disposed of as water-based waste paint. Dried material remnants can be disposed of as domestic waste.



Pack sizes: 2.5 litre and 10 litre

Surface coating system:

One to two consistent coats with undiluted LivingStyle COMPOSITION or diluted with max. 5% water.

A primer coat diluted with max. 5% water is to be applied first onto high-contrast surfaces and surfaces with a high or varying degree of absorbency.

Application:

Brush, roll or spray.

Clean the implements immediately after use with soap and water.

Usage:

Approx. 110-140 ml/m² per coat on a smooth surface. More on a rough surface as required.

Lower temperature limit during application:

+5 °C for surface and ambient air.

Drying time:

Surface-dry at +20 °C and 65% rel. humidity after 4–6 hours.

Paintable after 12 hours.

Hard-dry and resilient after approx. 3 days. These times are longer at lower temperatures and higher humidities.

Surfaces must be free of impurities and parting agents and must be dry.

Mineral mortar:

Paint solid, average absorbency mortar without pre-treatment. Apply solvent-free lay of Alpina Tiefgrund LF to porous, crumbling and absorbent mortar. Roughen and remove dust from gypseous, smooth ready-mixed mortar and apply a solvent-based primer.

Gypsum plasterboard:

Sand off trowel burr. Apply an undercoat of Alpina Tiefgrund LF.

Lime sand brick and exposed brickwork:

Paint without pre-treatment.

Stable old paint or resin mortar coatings:

Rework matt, slightly absorbent coatings directly.

Rough-off glossy old coats and rework to a stain-finish with LivingStyle COMPOSITION.

Unstable coatings:

Mechanically remove unstable old paint or coats of resin mortar by scratching, scraping, brushing or sand off and carefully remove dust.

Newly-coated woodchip, relief or Anaglypta from paper:

Paint without pre-treatment.

Non-adherent wallpapers: Remove completely. Wash-off all paste and paper residues, apply Alpina solvent-free primer.

Mildewed areas:

Remove mildew by washing/brushing off. Wash areas with Alpina mildew cleaner and allow to dry thoroughly.

It is advisable to determine and remedy the cause of the mildew where possible. Apply an undercoat of Alpina Bad- und Küchenfarbe.

Areas with nicotine traces:

Wash off stubborn impurities from smooth surfaces. Brush dry rough substrates.

Apply an undercoat of Alpina Nikotinsperre.

Small imperfections:

Carry out the appropriate preliminary work using a suitable mortar or filler and prime with Alpina solvent-free primer.

Technical Bulletin No. 5016_GB · Status: October, 2008

This Technical Bulletin has been compiled from state-of-the-art technology and our experience. Given the numerous substrates and property conditions, however, buyers/users are not relieved of their own obligation to check our materials for their suitability for the intended purpose.

Alpina Farben GmbH

D-64369 Ober-Ramstadt · Postfach 1220
Alpina Hotline Tel. No. +49(0)180 5/123 888
(€ 0.14/min. from a Deutsche Telekom landline, different tariff for calls from mobile phones)
www.alpina-farben.de